Borough of Manasquan Construction Department REQUIRED RESIDENTIAL UNIFORM CONSTRUCTION CODE INSPECTIONS

Inspections of 1 & 2 family dwellings for which construction must cease until the inspection is made is marked in bold
Steven J. Winters, CFM, Construction Official, Floodplain Administrator

		s, CFIVI, Construction Utticial, Floodplain Administrator	
<b>Building Subcode</b>			
INSPECTION TYPE	EXPLANATION		
FOOTING	The bottom of footing trenches before placement of footings		
FOOTING	(Pile Foundations only) Pile foundations require a pile log & certification prepared by a licensed design professional, collected after driven and BEFORE any vertical construction is started		
FOUNDATION	Foundations and all walls up to grade level prior to covering or back filling (new construction requires a foundation location survey at this point), reinforcement bars prior to concrete pour in walls		
Buildings located in	a flood hazard area: foundation location survey, including the lowest floor elevation and as-built elevation		
documentation, shall be submitted to the construction official/floodplain administrator <b>PRIOR TO FURTHER VERTICAL CONSTRUCTION</b> , and must include elevation certificates required by IBC 1612.4/IRC R322.1.10			
SLAB	Structural slab: Prior to the pouring of concrete and after the base course or subbase is properly prepared, and vapor barrier (if required) is in place and reinforcing materials such as rebar or wire mesh is properly positioned		
SILL PLATE or	Bolting of Sill Plates must be inspected prior to rendering them inaccessible or not readily accessible, or		
OPEN DECK	if rendered inaccessible after completion of framing		
SHEATHING	Sheathing of walls and roofs		
FRAMING	All structural framing, wind tie downs and strapping, framing connections (after all roughs pass)		
FRAMING	Buildings with truss systems: a truss system and permanent truss bracing inspection prior to the installation of any interior roof truss covering material		
BARRIER FREE	Barrier Free Subcode inspection for buildings required by N.J.A.C. 5:23-7.1 to be accessible		
INSULATION	✓ Inspection of Insulation prior to closing of the walls and ceilings		
	<ul> <li>Inspection of realing (air tightness) of the building thermal envelope. Also requires blower door test</li> </ul>		
ENERGY	<ul> <li>Duct tightness requires an air leakage test (post construction or during rough-in)</li> </ul>		
FINAL	<ul> <li>Installation of all interior/exterior finish materials, sealing of exterior joints, mechanical systems/equipment</li> <li>Final Barrier Free Subcode, for all buildings required by N.J.A.C. 5:23-7.1 to be accessible</li> </ul>		
	✓ Verification of compliance with N.J.A.C. 5:23-3.5, Posting structures		
Electrical Subcode			
SERVICE	Installation of the electrical service up to and including the main service disconnect		
ROUGH	Wiring within walls, and sub-panel installation		
FINAL	Final wiring, final installation of equipment, devices, and fixtures		
Plumbing Subcode			
ROUGH	Gas/plumbing/sewer piping, utilities, pool drains, mechanical appliances		
FINAL	Piping, trim, and fixtures		
Fire Subcode			
ROUGH	Fireplace factory-built venting/chimneys & dryer vents in framed walls/ceilings, fire suppression systems		
FINAL		pression systems; heat producing devices; special inspections, if required	
In-ground Pools			
Building Subcode: PRE-COLLAR/COLLAR Pool Collar (foundational support) REQUIRED prior to backfill			
Building Subcode:			
5	al Subcode: BONDING Equipotential bonding grid prior to cover		
Retaining Walls in accordance with N.J.A.C. 5:23-2.14(g)			
Building Subcode: FOUNDATION     Upon completion of the stone base or footing			
Building Subcode:         RETAINING WALL         Upon completion of wall			
Electrical, Plumbing, Mechanical, Utility, Septic trenches			
Demolition of a Structure			
Building Subcode: DEMOLITION Upon removal of footing, foundation, structure, upon re-grading & removal of all debris			
Demolition of a Pool           Building Subcode: DEMOLITION         Upon removal of the pool and PRIOR to backfill			
		II OF INE POOF AND PRIOR TO DACKIII	

Please note that pursuant to N.J.A.C. 5:23-2.18(b)4, where buildings proposed for construction exceed two stories in height or by their nature pose complex or unusual inspection problems, the Construction Official or appropriate Subcode Official may specify additional inspections to the applicant in writing prior to the issuance of a permit and during construction in the case of unforeseeable circumstances. All required inspections must be requested in accordance with N.J.A.C. 5:23-2.18